

10 Type designation

MP XXX - XX - X - X

Series

Upper gauge pressure limit

1; 1,6; 2,5; 4; 6; 10; 16; 25;
40; 60; 100; 150 MPa

Operating ambient temperature range

Version 1 - from - 45 to + 125 °C;
Version 2 - from - 45 to + 155 °C;
Version 3 - from - 45 to + 200 °C

Circuit

0 - “closed bridge” circuit; 1 - “open bridge” circuit

Thread code

M1 - M10x1-8g (1-150 MPa, drawings 1, 2);
U1 - 3/8-24UNF-3A (1-150 MPa, drawings 1, 2);
U2 - 3/8-24UNF-2A (1-150 MPa, drawings 1, 2);
M2 - M8x1-8g (1-25 MPa, drawing 3);
U3 - 5/16-24UNF-2A (1-25 MPa, drawing 3);
M3, M4, M5, M6 - M5x0,8-8g (1-10 MPa, drawings 4-7);
U4, U5, U6, U7 - 10-32UNF-2A (1-10 MPa, drawings 4-7)

Electrical connection

L - flexible wire 80 mm length; P - pin 2,3-2,9 mm height

Order example of pressure sensor

Pressure sensor of MP series, intended for pressure conversion from 0 to 60 MPa, for operation within temperature range from - 45 to + 200 °C, with “open bridge” circuit, 3/8-24UNF-2A thread and flexible wire 80 mm length:


Pressure sensor MP 60-31-U2-L.

Note: if wished, the wire length (standard 80 mm) can be changed, in this case the required length should be added to the wire code L, for example:

Pressure sensor MP 60-31-U2-L120.

11 Marking

Marking on the sensor body must contain following information: series, upper gauge pressure limit is in MPa, version of the operating temperature range, circuit type, thread code and order number



Microtensor

Pressure sensors MP Series